

SPECIFICATIONS

MODELS	DT40WR			DT40W			DT30		DT15	DT9.9	DT2.2							
TRANSOM HEIGHT (in.)	S:15 L:20 L2:22 LL:23 UL:25																	
STARTING SYSTEM	Electric			Electric			Manual		Electric		Manual							
WEIGHT kg (lbs.)	S: 75.0 (165.3) L: 76.0 (167.5) L2: 77.0 (169.8) LL: 78.0 (172.0) UL: 79.0 (174.2)			S: 79.0 (174.2) L: 80.0 (176.4) L2: 81.0 (178.6) LL: 82.0 (180.8) UL: 83.0 (183.0)			S: 75.0 (165.3) L: 76.0 (167.5) L2: 77.0 (169.8) LL: 78.0 (172.0) UL: 79.0 (174.2)		S: 60.5 (133.4) L: 61.5 (135.6) LL: 62.0 (136.7) UL: 62.5 (137.8)		S: 56.5 (124.6) L: 57.5 (126.8) LL: 58.0 (127.9) UL: 58.5 (129.0)		S: 38.5 (84.9) L: 39.5 (87.1)		S: 38.5 (84.9) L: 39.5 (87.1)		S: 12.0 (26.5)	
ENGINE TYPE	2-Stroke 2 Cylinders											2-Stroke 1 Cylinder						
PISTON DISPLACEMENT cm ³ (cu.in.)	696 (42.5)						499 (30.5)				284 (17.3)		55 (3.1)					
BORE x STROKE mm (in.)	79 x 71 (3.11 x 2.80)						71 x 63 (2.80 x 2.48)				59 x 52 (2.32 x 2.05)		41 x 37.8 (1.61 x 1.49)					
MAXIMUM POWER kW (PS)	29.4 (40)						22.1 (30)				11.0 (15)		7.3 (9.9)		1.6 (2.2)			
FULL THROTTLE OPERATING RANGE (rpm)	5,000-5,600						4,800-5,600				4,500-5,500		4,700-5,300					
FUEL TANK CAPACITY ℓ (US/imp.gal.)	25 (6.6/5.5)											1.2 (0.3/0.3)						
IGNITION SYSTEM	SUZUKI P.E.I.																	
BATTERY CHARGING	12V 80W						12V 80W or 30W						—					
STEERING	Remo-Con			Tiller Handle								Tiller Handle (Full Pivot Steering)						
TRIM METHOD (POSITIONS)	Manual Trim and Tilt (5)											Manual Trim and Tilt (4)						
FUEL/OIL MIXING RATIO	50 : 1*																	
GEAR SHIFT	F-N-R											Forward						
GEAR RATIO	11:23 (2.09)						12:23 (1.92)											
DRIVE PROTECTION	Rubber hub											Shear Pin						
PROPELLER SIZE in** (IDENTIFICATION NUMBER)	11-1/2 x 9 (S900)			11-1/2 x 10 (S1000)			10-1/4 x 10 (P1001)		10-1/4 x 11 (P1101)		9-1/4 x 7 (M701)		9-1/4 x 9 (M901)		7-3/8 x 4-1/2 (A400)			
	11-1/2 x 11 (S1100)			11-5/8 x 12 (S1200)			10-1/4 x 12 (P1201)		10-1/4 x 13 (P1301)		9-1/4 x 10 (M1001)		9-1/4 x 11 (M1101)					
	11-1/2 x 13 (S1301)			11-3/8 x 14 (S1400)			10-1/4 x 14 (P1401)				● 9-1/4 x 8 (M811)		● 9-1/4 x 9 (M911)					
	11-1/4 x 15 (S1500)			11-1/8 x 16 (S1600)			● 10-1/4 x 10 (P1011)		● 10-1/4 x 9 (P911)		● 9-1/4 x 10 (M1011)							
							● 10-1/4 x 12 (P1211)											

* 50:1 With Suzuki "C.C.I." oil or NMMA (National Marine Manufacturers Association) certified TC-W3TM Oil. ** Select the propeller which fits within the range of the engine rpm of each model.

FEATURES

MODELS	DT40WR	DT40W	DT30	DT15	DT9.9	DT2.2
Over-Rev Limiter	Std.Equip		—			
Emergency Stop Switch			Std.Equip		—	
Start-in Gear Protection			Std.Equip		—	
Shallow Water Drive	Optional Equip			Std.Equip		
Loop Charge Fuel Induction				Std.Equip		
Dual Water Intakes	Std.Equip			—		
Through Prop Hub Exhaust				Std.Equip		—
S.S. Water Pump Housing				Std.Equip		—
Anti-Corrosion System	Std.Equip					

Kerosene SPECIFICATIONS

MODELS	DT40WK	DT15K	DT9.9K
TRANSOM HEIGHT (in.)	S:15 L:20 L2:22 LL:23 UL:25		S:15 L:20
STARTING SYSTEM	Manual		
WEIGHT kg (lbs.)	S:76.0 (167.5) L:77.0 (169.8) L2:78.0 (172.0) LL:79.0 (174.2) UL:80.0 (176.4)		S:38.5 (84.9) L:39.5 (87.1)
ENGINE TYPE	2-Stroke 2 Cylinders		
PISTON DISPLACEMENT cm ³ (cu.in.)	696 (42.5)		284 (17.3)
BORE x STROKE mm (in.)	79 x 71 (3.11 x 2.80)		59 x 52 (2.32 x 2.05)
MAXIMUM POWER kW (PS)	29.4 (40)		11.0 (15) 7.3 (9.9)
FULL THROTTLE OPERATING RANGE (rpm)	5,000-5,600		4,500-5,500
FUEL TANK CAPACITY ℓ (US/imp.gal.)	Gasoline 12 (3.2/2.6) Kerosene 25 (6.6/5.5)		N/A Gasoline 12 (3.2/2.6) Kerosene 25 (6.6/5.5)
IGNITION SYSTEM	SUZUKI P.E.I.		
BATTERY CHARGING	12V 80W		12V 80W or 30W
STEERING	Tiller Handle		
TRIM METHOD (POSITIONS)	Manual Trim and Tilt (5)		
FUEL/OIL MIXING RATIO	30 : 1 (Gasoline & Kerosene)		
GEAR SHIFT	F-N-R		
GEAR RATIO	11:23 (2.09)		12:23 (1.92)
DRIVE PROTECTION	Rubber hub		
PROPELLER SIZE in** (IDENTIFICATION NUMBER)	11-1/2 x 9 (S900)		9-1/4 x 7 (M701)
	11-1/2 x 10 (S1000)		9-1/4 x 9 (M901)
	11-1/2 x 11 (S1100)		9-1/4 x 10 (M1001)
	11-5/8 x 12 (S1200)		9-1/4 x 11 (M1101)
	11-1/2 x 13 (S1301)		● 9-1/4 x 8 (M811)
	11-3/8 x 14 (S1400)		● 9-1/4 x 9 (M911)
	11-1/4 x 15 (S1500)		● 9-1/4 x 10 (M1011)
	11-1/8 x 16 (S1600)		

** Select the propeller which fits within the range of the engine rpm of each model.

Kerosene FEATURES

MODELS	DT40WK	DT15K	DT9.9K
Over-Rev Limiter	Std.Equip		—
Start-in Gear Protection			Std.Equip
Shallow Water Drive	Optional Equip		Std.Equip
Loop Charge Fuel Induction			Std.Equip
Dual Water Intakes	Std.Equip		—
Through Prop Hub Exhaust			Std.Equip
S.S. Water Pump Housing			Std.Equip
Anti-Corrosion System	Std.Equip		

STANDARD SERVICE TOOL KIT

- BOX WRENCH (10 x 12mm)
- BOX WRENCH (21mm)
- BOX WRENCH HANDLE
- COMBINATION SCREWDRIVER
- SCREWDRIVER HANDLE
- PLIERS
- EMERGENCY STARTER ROPE
- TOOL BAG

OPTIONAL PARTS CHART

MODELS	40WR	40WE	40W	30E	30	15/9.9	2.2
Speedometer	○	○	○	○	○	○	○
Remote control unit	STD	○	○	○	○		
Drag link	STD						
Voltage regulator	○	○	○	○	○	○	○
Rectifier	STD	STD	○	STD	○	○	○
Remote control attachment	STD	○	○	○	○		
Oversize piston & piston ring	○	○	○	○	○	○	○

STD: Standard Equip. ○: Optional Equip.